

Model Number
EX171A01

CHARGE OUTPUT PRESSURE SENSOR

Revision: NR
ECN #: 52823

Performance

	ENGLISH	SI	
Sensitivity(± 30 %)	1,200 pC/psi	174 pC/kPa	
Measurement Range	10 psi	68.9 kPa	
Maximum Pressure(static)	600 psi	4,136 kPa	
Resonant Frequency	≥ 25 kHz	≥ 25 kHz	
Rise Time(Reflected)	≤ 10 μ sec	≤ 10 μ sec	
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS	[1]

Environmental

Acceleration Sensitivity	< 0.01 psi/g	< 0.007 kPa/(m/s ²)	
Temperature Range(Operating)	0 to 500 °F	-18 to 260 °C	
Temperature Coefficient of Sensitivity	≤ 0.08 %/°F	≤ 0.144 %/°C	
Maximum Shock	1,000 g pk	1,000 g pk	
Hazardous Area Approval	See Manual	See Manual	

Electrical

Output Polarity	Differential	Differential	
Capacitance	12,000 pF	12,000 pF	[2]
Electrical Isolation	≥ 10 ⁸ Ohm	≥ 10 ⁸ Ohm	
Internal Resistance(room temp)	≥ 1 GOhm	≥ 1 GOhm	
Internal Resistance(@500F)	≥ 500 kohm	≥ 500 kohm	

Physical

Sensing Geometry	Compression	Compression	
Housing Material	316L Stainless Steel	316L Stainless Steel	
Diaphragm	316L Stainless Steel	316L Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Weight	6.5 oz	185 gm	[2]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

- [1]Zero-based, least-squares, straight line method.
- [2]Typical.
- [3]See PCB Declaration of Conformance PS132 for details.
- [4]See Model's "Instructions For Use" (IFU) for North American Conformity and Certification Statements.

SUPPLIED ACCESSORIES:

Model 31061-01 SEAL, 1.370" OD x 1.130" ID x.030", BRASS (2)



Entered: ND	Engineer: RPF	Sales: MV	Approved: RPF	Spec Number:
Date: 05/12/2022	Date: 05/12/2022	Date: 05/12/2022	Date: 05/12/2022	76249



Intertek [4]

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.



3425 Walden Avenue, Depew, NY 14043